

ZEPHIR MODEL RANGE

Model	Train weight	Drawbar	LOK weight	Dimensions	(Diesel)	(Diesel)	(Electric)	(Electric)	(Electric)
LOK30	5600 t	280 kN	48 t	7360x2500x3660 mm	25 km/h	362kW	14 km/h	50x2 kW	4185 Ah
LOK22	4600 t	230 kN	40 t	7000x2500x3630 mm	25 km/h	362 kW	14 km/h	50x2 kW	4185 Ah
LOK20	4000 t	200 kN	35 t	7000x2500x3630 mm	25 km/h	224 kW	16 km/h	50x2 kW	4185 Ah
LOK16	3200 t	160 kN	29 t	6500x2500x3410 mm	25 km/h	224 kW	16 km/h	50x2 kW	4185 Ah
LOK13	2600 t	130 kN	24 t	4800x2500x3400 mm	25 km/h	160 kW	17 km/h	32x2 kW	1920 Ah
LOK10	2000 t	100 kN	20 t	4800x2500x3400 mm	25 km/h	129 kW	17 km/h	32x2 kW	1920 Ah

May speed

EQUIPMENT ONBOARD

Comfort cabin 360 degrees
1520mm gauge with stone catchers
SA-3 couplers with remote activation
Arctic plug-in pack for Nordic climate
Pneumatic braking system 1.540, 2200 l/min
Double air brake hoses
Train brake line power release system
Air blade rail cleaning system
Traction performance system
Wheels anti-spin system

ZEPHIR safety package

Telemetrics remote diagnostics system

Driver identity system, PIN protected

In-railing and rear-view video cameras

Rail signalling lights, beacon, buzzer

Additional working lights

Rail track short circuiting system

Diesel engine start-stop system

On-board battery charging system

CE certificate, Manuals, Drawings

OPTIONS

Remote control

Railtrack signalling system

Distance proximity sensors

In-railing video camera system

Data logger

Multi-Unit configuration

Rear-drive control unit and seat

Hybrid pack with diesel generator

Extended warranty

Other options upon request

